



Product Service

CERTIFICATE

No. Z1A 090361 0044 Rev. 00

Holder of Certificate: **Kinnarps AB**

Industrigatan 1
521 88 Kinnarp
SWEDEN

Certification Mark:



Product:

Office chairs
Office work chairs

Tested according to:

DIN EN 1335-1:2023
DIN EN 1335-2:2019
PPP 51054D:2023
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713281751

Valid until: 2029-04-29

Date, 2024-04-30

(Jens Biesenack)

CERTIFICATE

No. Z1A 090361 0044 Rev. 00

Model(s): **Plus [6]**
6770, 6772, 6774, 6780, 6782, 6784

Parameters:

| | |
|----------------------------------|---|
| Type Overview | 6770: with low backrest and without armrest 6772: with low backrest and 2D armrest 6774: with low backrest and 4D armrest 6780: with high backrest and without armrest 6782: with high backrest and 2D armrest 6784: with high backrest and 4D armrest |
| Seat | Upholstered, adjustable in height and depth, synchrone mechanism |
| Seat height adjustment | 400 – 535 mm By gas spring S.C. Stabilus Romania S.R.L. Tube type: STAB-O-MAT D; material 0106184, Outside diameter: 28 mm Wall thickness: 2.5 mm; Surface finish: plasma nitrified |
| Seat depth | 425 – 520 mm |
| Backrest | Upholstered |
| Headrest | Optional |
| Backrest height (above seat) | 555 mm (6770 / 6772 / 6774) or 605 mm (6780 / 6782 / 6784) |
| Backrest width | 415 mm |
| Armrest (optional) | Plastic frame and armrest pad, 2D or 4D armrest |
| Distance between armrests | 410 – 520 mm (2D) or 335 – 520 mm (4D) |
| Armrest height | 165 – 290 mm |
| Armrest length | 235 mm (2D) or 254 mm (4D) |
| Base | Plastic or aluminium |
| Maximum offset of the underframe | 364 mm |
| Swivel chair type | Type A (according to DIN EN 1335-1:2023) |